

November 14, 1958

GENERAL  ELECTRIC

B50E73

TRANSPORTATION SYSTEMS BUSINESS DIVISION
SPECIFICATION AND PROPERTIES

S 4

Orders and Correspondence Must
Specify Complete Number

TITLE

PERFORATED STEEL SHEETS

GE Material B50E73 identifies commercial perforated steel sheets the conditions of which are designated as follows:

Perforations

<u>GE Material</u>	<u>Diameter</u>	<u>Spacing (1)</u>	<u>Open</u>
B50E73A	1/8"	3/16" centers	40%
B50E73B	1/4"	3/8" centers	40%
B50E73C	3/8"	1/2" centers	51%
B50E73D	1/2"	11/16" centers	47%
B50E73E	5/8"	13/16" centers	54%
B50E73F	1/16"	3/16" centers	10%
B50E73G	3/16"	1/4" centers	51%

(1) Staggered

*General Requirements

Material shall be hot rolled low-carbon sheet steel, pickled and oiled, equivalent to GE Material B8A3A.

Perforated sheets shall be free from burrs or other imperfections which might affect their serviceability or appearance.

Packing and Marking

Material shall be suitably packed to prevent damage during transit. Each package, box, crate, etc., shall be marked with the purchase order number, the manufacturer's name, the GE material designation, and the weight.

*Required by Specification